



Electrolux

air-o-convect LPG Gas Convection Oven 20GN 2/1

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



air-o-convect

LPG Gas Convection Oven 20GN 2/1

269715 (AOS202GCD2)

air-o-convect, gas (LPG),
20x2/1GN, convection oven
with direct steam and 11
humidity level settings

Short Form Specification

Item No.

Convection oven with direct steam: 90% steam saturation in 4 minutes.
air-o-flow: fresh air is blown into the oven from the outside, after it is pre-heated it is pulled through the bi-functional fan, guaranteeing cooking evenness. Manual injection of water to add additional moisture in the cell.

air-o-clean: built-in cleaning system with four automatic pre-set cycles and one semi-automatic cleaning cycle.

Cooking cycles: hot air (max 300 °C) combined with 11 different humidity settings, ranging from browning to baking and par-steaming. 2-step cooking with the possibility to combine different cycles. Full speed and pulse ventilation controls. Food probe for precise cooking. Double-glass door with book-like opening maintains a cool external temperature and incorporates a drip pan to collect excess condensation avoiding wet floors. Halogen lighting in the cooking chamber. Side panels and interior in AISI 304 stainless steel. Supplied with n.1 trolley rack 2/1GN, 63mm pitch and door shield.

Main Features

- Dry hot convection cycle (max 300 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation:
 - 0 = no additional moisture (browning, au gratin, baking, pre-cooked food)
 - 1-2 = low moisture (small portions of meat and fish)
 - 3-4 = medium low moisture (large pieces of meat, reheating, roasted chicken and proving)
 - 5-6 = medium moisture (roasted vegetable and first step of roasted meat & fish)
 - 7-8 = medium-high moisture (stewed vegetables)
 - 9-10 = high moisture (poached meat and jacket potatoes)
- air-o-clean™ automatic and built-in self cleaning system (4 automatic and 1 semi-automatic cycles).
- air-o-flow: fresh air from the outside is directed to the bi-functional fan, becomes pre-heated and then pushed into the cooking chamber to guarantee an even cooking process.
- Double step cooking to set two different phases.
- Variable fan speed (radial fan): full speed or pulse ventilation for baking and slow cooking.
- Exhaust valve electronically controlled to extract humidity in excess for extra crispy results.
- Automatic and manual rapid cooling activation when going from a higher to a lower temperature.
- Gas burner is certified by Gastec for high efficiency and low emissions.
- Single sensor core temperature probe included.
- Supplied with n.1 trolley rack 2/1GN, 63mm pitch and door shield.

Construction

- IPX 5 spray water protection certification for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Seamless hygienic cooking chamber with all rounded corners for easy cleaning.
- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Swing hinged front panel for easy service access to main components.

APPROVAL: _____



Electrolux

LPG Gas Convection Oven 20GN 2/1
air-o-convect



Included Accessories

- 1 of Trolley with tray rack for 20x2/1GN ovens and bcf, 63mm pitch PNC 922044
- 1 of Control panel filter for 20xGN2/1 ovens (already included) PNC 922249

Optional Accessories


- Water softener with cartridge C500 for 6 1/1 and 10 1/1 ovens (low-medium steam usage - less than 2hrs per day full steam) PNC 920002
- Water softener with cartridge STEAM 1200 PNC 920003
- Automatic water softener for ovens PNC 921305
- Resin sanitizer for water softener PNC 921306
- Pair of 1/1 GN AISI 304 grids PNC 922017
- Couple of grids for whole chicken 1/1GN (8 per grid) PNC 922036
- Trolley with tray rack for 20x2/1GN ovens and bcf, 63mm pitch PNC 922044
- Trolley with tray rack for 16x2/1GN ovens and bcf, 80mm pitch PNC 922046
- Thermal blanket for 20x2/1GN PNC 922049
- Trolley with banquet rack 92 plates for 20x2/1GN ovens and bcf, 85mm pitch PNC 922055
- Pastry trolley for 20x2/1GN ovens and bcf, 80mm pitch (16 runners). Suitable for 600x400mm pastry trays in oven PNC 922069
- Door shield for pre-heating oven, without trolley, 20 GN 2/1 PNC 922095
- Side external spray unit (needs to be mounted outside and includes support for mounting to oven) PNC 922171
- Pair of 2/1GN aisi 304 stainless steel grids PNC 922175
- 2 fat filters for 20 1/1 and 2/1 GN combi steamers (gas and electric) and convection ovens (electric) PNC 922179
- Baking tray with 5 rows (baguette), perforated aluminium with silicon coating (400x600x38) PNC 922189
- Baking tray with 4 edges, perforated aluminium (400x600x20) PNC 922190
- Baking tray with 4 edges, aluminium (400x600x20) PNC 922191
- Basket for detergent tank - wall mounted PNC 922209
- Flue condenser for gas combi steamers and convection ovens PNC 922235
- 2 frying baskets for ovens PNC 922239
- Heat shield for 20x2/1GN PNC 922242
- Retractable spray unit for 20GN1/1&2/1 ovens PNC 922263
- Grid for whole chicken 1/1GN (8 per grid - 1,2kg each) PNC 922266
- Kit integrated HACCP for ovens PNC 922275
- Kit to convert from LPG to natural gas PNC 922278
- Adjustable wheels for 20x1/1 and 20x2/1GN ovens PNC 922280

- Baking tray for baguette 1/1GN PNC 922288
- Egg fryer for 8 eggs 1/1GN PNC 922290
- Kit universal skewer rack and 6 short skewers for Lengthwise and Crosswise ovens PNC 922325
- Universal skewer rack PNC 922326
- 6 short skewers PNC 922328
- Grease collection tray 40 mm PNC 922329
- Smoker for lengthwise and crosswise ovens - 4 kinds of smoker wood chips are available on request PNC 922338
- Water nanofilter for ovens (10x2/1GN, 20x1/1GN and 20x2/1GN) PNC 922344
- External reverse osmosis filter for ovens (10x2/1GN, 20x1/1GN and 20x2/1GN) PNC 922345
- Chimney adaptor PNC 922346
- Kit check valve PNC 922347
- Multipurpose hook PNC 922348
- Flat baking tray with 2 edges, GN 1/1 PNC 925006

Front

Top


CWI1 = Cold Water inlet 1
 CWI2 = Cold Water Inlet 2
 D = Drain
 EI = Electrical connection

G = Gas connection

Side

Electric

Supply voltage:
 269715 (AOS202GCD2) 230 V/1N ph/50/60 Hz

Electrical power: 2 kW

Circuit Breaker required

Gas

ISO 7/1 gas connection diameter: 1" MNPT

LPG:

Pressure: 11" w.c. (27.4 mbar)

Heating elements: 187495 BTU (55 kW)

Total thermal load: 187495 BTU (55 kW)

Water:

Water inlet "CW" connection: 3/4"

Total hardness: 5-50 ppm

Pressure, bar min/max: 1.5-4.5 bar

Drain "D": 2"

Electrolux recommends the use of treated water, based on testing of specific water conditions.
 Please refer to user manual for detailed water quality information.

Installation:

Clearance: 5 cm rear and right hand sides.

Suggested clearance for service access: 50 cm left hand side.

Capacity:

GN: 20 - 2/1 Gastronorm

GN: 40 - 1/1 Gastronorm

Max load capacity: 200 kg

Key Information:

External dimensions, Height: 1795 mm

External dimensions, Width: 1243 mm

External dimensions, Depth: 1107 mm

Net weight: 378 kg

Shipping weight: 408 kg

Shipping volume: 3.1 m³