



Electrolux

Prostore 500 1 Glass Door Digital Refrigerator, 470lt (0/+10 °C) - R290

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Prostore 500

1 Glass Door Digital Refrigerator, 470lt (0/+10 °C) - R290

691237 (PS04RIG)

1-glass door prostore cabinet 470lt, 0/+10°C, AISI 304, R290

Short Form Specification

Item No.

Full glass door refrigerator constructed in 304 AISI stainless steel with external bottom panel in anti-corrosive material. Large digital display featuring humidity selection button (3 preset level), cabinet temperature display and setting and turbo frost cycle (to rapidly cool warm loads). HACCP-compliant control with alarms and history. Frost Watch Control to defrost only when required with automatic evaporation of defrost water. Optimized airflow provides even temperature distribution on all grids. Fitted with 65 mm-thick polyurethane insulating foam. Features door microswitch to switch off the fan when the door is opened. Hidden evaporator to guarantee higher storage capacity and less corrosion problems. Built-in refrigeration unit; ventilated operation; Internal all-round door LED lighting for best visibility. For ambient temperatures up to 32 °C. CFC and HCFC free. R290 highly ecological refrigerant type, cyclopentane gas in foam. Supplied with 5 x 520X442mm Rilsan coated grids and n. 5 sets of 2 stainless steel grid runners. Prearranged to fit RS485 port to facilitate connection to a remote computer and integrated HACCP systems.

Main Features

- Large digital white-digit display with humidity selection button (3 preset level), cabinet temperature display and setting and turbo frost cycle (to rapidly cool warm loads).
- Fully compliant HACCP digital control: when temperature exceeds critical limits, acoustic and visual alarms are activated. Up to two months of event are kept in memory.
- Large storage area suitable to contain 520x442 mm grids or shelves to improve net capacity.
- Optimized airflow within the chamber guarantees uniformity of temperature on all grids.
- Frost Watch Control: fully automatic defrost starts only when ice is actually building-up in the evaporator and adapt the defrosting duration to guarantee perfect ice removal while optimizing energy efficiency consumption.
- CFC and HCFC free (highly ecological refrigerant type: R290, - ecological gas in foam: cyclopentane).
- Hidden evaporator thus guaranteeing higher storage capacity and less corrosion problems.
- Greater storage space: internal structure with numerous charging positions available to host grids, ensuring higher net capacity.
- Adjustable temperature range from 0°C to +10°C.
- Suitable for use in ambient temperatures of up to 32 °C.
- Insulation thickness: 65 mm of polyurethane injected with ecological foaming gas cyclopentane to ensure effective insulation with minimum energy consumption (thermal conductivity: 0,020 W/m*K).
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption and ease of cleaning.
- Cleaning-free condenser: the structure of the wire frame condenser prevents dust and grease accumulation thus avoiding periodical cleaning operations and reducing energy consumption.
- Optical door microswitch to stop the fan once the door is opened, thus minimizing energy waste.
- Model requires only 1 phase 230V/50Hz supply and can be plugged straight into an existing power socket.
- Automatic evaporation of the defrosting water by hot gas on the top for energy saving.
- Internal all-round door LED lighting for best visibility.
- Prearranged to fit RS485 port to facilitate

APPROVAL: _____



Electrolux

Prostore 500
1 Glass Door Digital Refrigerator, 470lt (0/+10 °C) - R290



Electrolux

**Prostore 500
1 Glass Door Digital Refrigerator,
470lt (0/+10 °C) - R290**

connection to a remote computer and integrated HACCP systems.

- Complies with main international certification bodies and is CE marked.
- Low noise level.
- IPX5 frontal water protection.
- Tropicalized unit (43°C ambient temperature).
- This appliance is intended for use in ambient temperatures up to 40°C.



**Prostore 500
1 Glass Door Digital Refrigerator, 470lt (0/+10 °C) - R290**

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2016.07.28



Construction

- Stainless steel AISI 304 external panels (galvanized external back).
- Inner cell with rounded corners, bottom pressed in only one piece.
- Stainless steel runners and supports easily disassembled.
- Internal components removable without the use of tools to facilitate cleaning operations.
- Pressed stainless steel door handle without joints gathering dust and dirt.
- Easy access to the main components for maintenance.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.



Included Accessories

- 5 of Plastic coated grid (520x442) PNC 880319
- 5 of Pair of runners for 470 and 720lt prostore cabinets PNC 880335


Optional Accessories

- Kit integrated HACCP for digital refrigerators (IR33) PNC 880252
- Plastic coated grid (520x442) PNC 880319
- Stainless steel grid (520x442) PNC 880321
- Kit 4 feet, height 200mm PNC 880325
- Kit of 4 feet-h=67 (marine) PNC 880326
- Kit pair of runners (marine) PNC 880327
- Base frame for 1/1 GN rack for 470lt prostore PNC 880328
- Pair of runners for 470 and 720lt prostore cabinets PNC 880335
- Printer for HACCP basic version (for cabinets and counters with digital control) PNC 881457



Front

Top


EI = Electrical inlet (power)
RI = Refrigerant Inlet
RO = Refrigerant Outlet

Side


Electric

Supply voltage:
691237 (PS04RIG) 230 V/1N ph/50 Hz
Electrical power max.: 0.207 kW

Key Information:


Gross capacity: 470 lt
Net Volume: 316 lt
Door hinges: Right Side
External dimensions, Height: 2040 mm
External dimensions, Width: 600 mm
External dimensions, Depth: 700 mm
External dimensions, Depth with Doors Open: 1226 mm
Number and type of doors: 1 Glass
Internal Dimensions (depth): 582 mm
Internal Dimensions (height): 1474 mm
Internal Dimensions (width): 472 mm
Noise level: 52 dBA
Height adjustment: 15/40 mm
Number and type of grids (included): 5 - 520x442
Type of external material: 304 AISI
Type of internal material: 304 AISI
Number of positions & pitch: 44; 22 mm

Refrigeration Data

Control type: Digital
Compressor power: 1/4 hp
Refrigerant type: R290
Refrigeration power: 320 W
Refrigeration power at evaporation temperature: -10 °C
Refrigerant weight: 90 g
Operating temperature min.: 0 °C
Operating temperature max.: 10 °C
Operating mode: Ventilated
Cooling unit: Built-In
Defrost type: By Air

Product Information (EU Regulation 2015/1094)

Energy Class: g
Yearly energy consumption: 1270kWh/year
Climate class: Heavy Duty (5)
Energy Efficiency Index (EEI): 112,57



EU energy labelling from 1st July 2016

The European energy labelling scheme for professional refrigerators and freezers is based on requirements setting Minimum Energy Performance standards for commercial refrigeration cabinets sold within the EU. These requirements are designed to drive energy efficiency and environmentally friendly approach for professionals. The European energy labelling scheme will apply to all manufacturers and importers who sell and market products within the EU and it is mandatory across Europe.

Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.