

Washer extractor

W5130N

Features and benefits

- **Compass Pro[®] microprocessor offers:**
 - Large display and one control knob for easy program selection
 - Language selection
 - Quick selection and option buttons for the most frequently used wash programs and options
- Extremely low water and energy consumption – see table below
- Four compartment detergent box for manual dosing of powder or liquid detergent
- High extraction force for efficient dewatering
- Door with gasket and strong hinges built for heavy duty operation
- Stainless and galvanized steel in all vital parts for high degree of rust protection
- SuperBalance guarantees the correct extraction force

Main options

- Automatic liquid detergent supply (optional I/O board)
- Connection to booking- /payment- system or coin meter



Images shown are a representation of the product only and variations may occur.

Main specifications				W5130N			
Max. capacity	filling factor 1:9	kg/lb		14/30			
Drum, volume		litre/ft ³		130/4.6			
	diameter	ø mm/inch		595 / 23 7/16			
Extraction		rpm		548			
G-factor				100			
Standard heating alternatives	electricity	kW		7.5 / 10.0			
Low energy heating alternatives	electricity	kW		3.0			
	steam			x			
	non-heated			x			
Consumption data 6S03				EI		Steam**	
"Warm" *				Full load, 14 kg / 30 lb	Half load, 7 kg / 15 lb	Full load, 14 kg / 30 lb	Half load, 7 kg / 15 lb
Total time		min		32	30	32	30
Water consumption (cold+hot)		litre/gallon		197/52 + 12/3	161/43 + 12/3	209/55 + 0/0	173/46 + 0/0
Energy consumption (motor/heating/hot water)		kWh		0.15/1.2/0.75	0.1/0.75/0.75	0.15/-	0.1/-
Steam consumption		kg/lbs		-	-	2.9/6.4	2.3/5.1
Residual moisture		%		77	84	77	84

* Water temperature 59°F cold water and 149°F hot water.

** Depending on steam pressure.

Electrical connections					
Heating alternative	Main voltage		Heating power kW	Total power kW	Recommended ITCB A
		Hz			
Electric heated	208-240V 1 -	60	3.0/7.5/10.0	3.3/7.8/10.3	25/50/60
	208-240V 3 -	60	3.0/7.5/10.0	3.3/7.8/10.3	15/25/35
	440/480V 3 -	60	7.5/10.0	7.8/10.3	15/20
Steam or Non heated	120/440/480V -	60	-	0.9	15
	208-240V -	60	-	0.8	15

Water and steam connection		W5130N
Water valves	DN/inch	20 / 3/4
Water pressure	psi	30-90
Capacity at 300 kPa	l/min	20
Drain valve	ø mm/inch	75 / 3
Draining capacity	l/min	170
Steam valve	DN/inch	15 / 1/2
Steam pressure	psi	40-90
Liquid detergent supplies		5
Floor requirements		
Frequency of the dynamic force	Hz	9.1
Floor load at max extraction	kN	2.4 ± 3.1
Sound levels		
Sound power/pressure level at extraction*	dB(A)	68/53
Sound power/pressure level at wash*	dB(A)	62/47
Heat emission		
% of installed power, max		5
Shipping data**		
Weight	net, kg/lbs	154 / 340
Shipping volume	m ³ /ft ³	1.02 / 36
Accessories		
Steel base		x
Hose kits for water or steam		x
Fluff collector		x
Dimensions in mm/inch		
A Width		720 / 28 3/8
B Depth		787 / 31
C Height		1216 / 47 7/8
D1		367 / 14 7/16
D2		424 / 16 11/16
E		1337 / 52 5/8
F		920 / 36 1/4
G		80 / 3 1/8
H		1119 / 44 1/16
I		217 / 8 9/16
J		124 / 4 7/8
K		1099 / 43 1/4
L		999 / 39 5/16
M		278 / 10 15/16
N		103 / 4 1/16
O		212 / 8 3/8
1 Operating panel	6 Re-used water	
2 Door opening ø 365 mm / 14 3/8 inch	7 Drain	
3 Detergent box	8 Liquid detergent supply	
4 Cold water	9 Electrical connection	
5 Hot water	10 Steam connection	

Front and side panels in light grey and blue (RAL 260 70 05, 250 60 30)

* Sound power levels measured according to ISO 60704.

** Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

