



# HEAVY DUTY REFRIGERATED COLD WELL TABLES WITH ENCLOSED BASE



**HDRCP-3-BS Shown**

**FEATURES:**

- Heavy duty construction
- All welded 300 series stainless steel
- High nominal cooling capacity. (1500 btuh) for guaranteed product temperature control
- Aluminum encased copper tube evaporator panels improve heat transfer by increasing contact area
- This increases operating efficiency and reduces power consumption
- Expansion valve for efficient operation at various temperature conditions
- Refrigerant filter drier to insure cleanliness of sealed refrigeration circuit
- Sight glass to insure a properly charged refrigeration system
- Liquid receiver for improved refrigerant charge control
- Low running current suitable for any 115 volt circuit
- Precision electronic thermostat for exact temperature control
- Switched 115 VAC receptacles to power condensing unit and remote ventilation fan. (optional)
- Uses standard 12" x 20" pans, and smaller pans with the use of adapter bars

**For Mobile Units:**

- SU-25** - 5" swivel casters, two with brakes
- Universal mount push handle (right/left) on mobile units



Item #: \_\_\_\_\_ Qty #: \_\_\_\_\_  
 Model #: \_\_\_\_\_  
 Project #: \_\_\_\_\_

**NOTE: Units are not designed to cool foods originally warm. Food should already be chilled to maintain the proper temperatures**

**MATERIAL:**

**TOP:** 18 gauge, #304 stainless steel, with black polyethylene thermal breaker marine edge

**BODY:** 18 gauge #304 stainless steel

**LINER:** Constructed of 18 gauge, 304 stainless steel, with 3" recessed top, one piece construction, all welded, ground and polished to a uniform finish. All corners are covered with a 1/4" radius. Liner is pitched towards a 1" I.P.S. drain

**CUTTING BOARD:** Stainless steel shelf with 1/2" thick poly cutting board - Ships K.D.

**LEGS:** 16 gauge stainless steel with full adjustable stainless steel bullet foot

**REFRIGERATION SYSTEM:** The compressor is housed in a 16 gauge galvanized under structure, fabricated from formed angles and bolted to the galvanized jacket. The fully self contained condensing unit is provided with a hermetically sealed compressor with a digital, programmable thermostat. The system is fully charged with environmentally friendly R404-A refrigerant

**ELECTRICAL:**

- Unit will be wired for 15 amps, 120V single phase operation with an on/off thermostat switch
- 2-3 well Units: 115 V, 8 AMPS, 60 Hz, 1/4 HP
- 4-6 well Units: 115 V, 8 AMPS, 60 Hz, 1/3 HP
- Includes 6 ft. long, 3 wire cord with a NEMA 5-15P plug

Model	Length (L)	Width	Drain Distance (A)	Refrigerant	Wt (lbs.)	Cu. Ft.
HDRCP-2-BS	31.8125"	28.25"	27.35"	R404-A	320	24
HDRCP-3-BS	47.125"	28.25"	42.625"	R404-A	420	36
HDRCP-4-BS	62.50"	28.25"	57.975"	R404-A	510	50
HDRCP-5-BS	77.75"	28.25"	73.25"	R404-A	568	62
HDRCP-6-BS	93.125"	28.25"	98.50"	R404-A	633	74



**OPTIONAL CASTERS**  
 Visit our website for additional Food Table Accessories

SU-26



**Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.**

For Orders & Customer Service:  
 Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:  
 Email: smartfab@advancetabco.com or Fax: 631-586-2933

# DIMENSIONS and SPECIFICATIONS

TOL ± .125"

ALL DIMENSIONS ARE TYPICAL

## SIDE VIEW

