

Washer extractor

W5600X

Features and benefits

- **Compass Pro[®] microprocessor offers:**
 - Large display and one control knob for easy program selection
 - Language selection
 - Quick selection and option buttons for the most frequently used wash programs and options
 - Wash program packages optimized on Economy, Performance and Time. (Available on general programs)
- Extremely low water and energy consumption – see table below
- High extraction force for efficient dewatering
- Door with gasket and strong hinges built for heavy duty operation
- Stainless and galvanized steel in all vital parts for high degree of rust protection
- SuperBalance guarantees the correct extraction force



Images shown are a representation of the product only and variations may occur.

Main options

- Stainless steel side panels
- Coin-meter
- Five compartment supply injector
- Third water inlet valve

Main specifications				W5600X	
Max. capacity	filling factor 1:10	kg/lb		60/135	
Drum, volume		litre		600	
	diameter	ø mm		980	
Extraction		rpm		630	
G-factor				220	
Heating alternatives, 230/400V	electricity	kW		38/54	
	steam			x	
	non-heated			x	
Consumption data "Normal 60°C"				Full load, 60 kg	Half load, 30 kg**
Economy*					
Total time		min	51	49	
Water consumption (cold+hot)		litre	380+100	360+80	
Energy consumption (motor/heating/hot water)		kWh	0.75/2.85/6.4	0.7/2.3/5.1	
Steam consumption		kg	13.9	11.1	
Residual moisture		%	60	66	
* Water temperature 15°C cold water and 65°C hot water.					
** Depending on steam pressure.					

Electrical connections					
Heating alternative	Main voltage		Heating power kW	Total power kW	Recommended fuse A
		Hz			
Electric heated	220-230V 3 ~	50/60	35-38	36-40	100
	240V 3 ~	50/60	38	40	100
	380-400V 3 ~	50/60	35-38	37-40	63
	415V 3 ~	50/60	38	40	63
	380-415V 3 ~	50/60	51.7-54.0	53.7-56.0	100
Non heated or steam heated	220-415V 1/3 ~	60	-	2.6	10

Water and steam connection		W5600X
Water valves	DN	25
Water pressure	kPa	200-600
Capacity at 300 kPa	l/min	110
Drain valve	∅ mm	75
Draining capacity	l/min	170
Steam valve	DN	20
Steam pressure	kPa	300-600
Floor requirements		
Frequency of the dynamic force	Hz	10.5
Floor load at max extraction	kN	10 ± 15.6
Sound levels		
Sound power level (IEC 60704-2-4)		
wash	dB(A)	70
extraction	dB(A)	84
Heat emission		
% of installed power, max		5
Shipping data**		
Weight	net, kg	775
Shipping volume	m ³	3.2
Dimensions in mm		
A	Width	1173
B(a)	Depth	1951
B(b)	Depth	1193
C	Height	1673
D		33
E		93
F		600
G		540
H		1370
I		125
J		255
K		227
L		87
M		85
N		802
O		103
P		1544
Q		1361
R		587
1	Operating panel	6 Drain
2	Door opening ∅ 535 mm	7 Liquid detergent supply
3	Detergent box	8 Electrical connection
4	Cold water	9 Steam connection
5	Hot water	10 Detergent supply injector, powder, right or left side (option)

* Other voltages available, see installation manual

** Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

