



**ALVI Officine Meccaniche E. Viazzo & C. s.r.l.**  
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA  
Tel. +39 0161 234600 - Fax +39 0161 234633  
E-mail: [info@alvi-italia.com](mailto:info@alvi-italia.com) - [www.alvi-italia.com](http://www.alvi-italia.com)

**680 CR 2+2**

**RM0680ON186**

**Spring loaded bottom trolley**

Body in AlMg3 light alloy sheet, anodized (10 micron). Self-levelling platform with 2 side die-cast elements, complete with nylon rolls fit for sliding in light alloy rails, and 1 steel spring. Weight indicator. Strong non-twisting bottom iron frame in epoxy finishing. 2 fixed and 2 swivelling wheels with non-marking rubber ring and zinc-plated housings.



<b>Internal dimensions</b>	1000 x 420 x 530
<b>External dimensions</b>	1080 x 450 x 800 mm h
<b>Capacity</b>	223 l 32 kg
<b>Weight</b>	32 kg
<b>Wheels diameter</b>	100 mm
<b>Wheels position</b>	2 + 2



**ALVI Officine Meccaniche E. Viazzo & C. s.r.l.**  
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA  
Tel. +39 0161 234600 - Fax +39 0161 234633  
E-mail: [info@alvi-italia.com](mailto:info@alvi-italia.com) - [www.alvi-italia.com](http://www.alvi-italia.com)

**680 CR 2+2**

**RM0680ON014**

**Spring loaded bottom trolley**

Body in AlMg3 light alloy sheet, anodized (10 micron). Self-levelling platform with 2 side die-cast elements, complete with nylon rolls fit for sliding in light alloy rails, and 1 steel spring. Weight indicator. Strong non-twisting bottom iron frame in epoxy finishing. 2 fixed and 2 swivelling wheels with non-marking rubber ring and zinc-plated housings.



<b>Internal dimensions</b>	1000 x 600 x 560 mm h
<b>External dimensions</b>	1080 x 630 x 800 mm h
<b>Capacity</b>	336 l 47 kg
<b>Weight</b>	35,1 kg
<b>Wheels diameter</b>	125 mm
<b>Wheels position</b>	2 + 2



**ALVI Officine Meccaniche E. Viazzo & C. s.r.l.**

S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA

Tel. +39 0161 234600 - Fax +39 0161 234633

E-mail: [info@alvi-italia.com](mailto:info@alvi-italia.com) - [www.alvi-italia.com](http://www.alvi-italia.com)

**680 CR 2+2**

**RM0680ON013**

**Spring loaded bottom trolley**

Body in AlMg3 light alloy sheet, anodized (10 micron). Self-levelling platform with 2 side die-cast elements, complete with nylon rolls fit for sliding in light alloy rails, and 1 steel spring. Weight indicator. Strong non-twisting bottom iron frame in epoxy finishing. 2 fixed and 2 swivelling wheels with non-marking rubber ring and zinc-plated housings.



<b>Internal dimensions</b>	1390 x 700 x 560 mm h
<b>External dimensions</b>	1470 x 730 x 800 mm h
<b>Capacity</b>	545 l 95 kg
<b>Weight</b>	49,3 kg
<b>Wheels diameter</b>	125 mm
<b>Wheels position</b>	2 + 2



**ALVI Officine Meccaniche E. Viazzo & C. s.r.l.**

S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA

Tel. +39 0161 234600 - Fax +39 0161 234633

E-mail: [info@alvi-italia.com](mailto:info@alvi-italia.com) - [www.alvi-italia.com](http://www.alvi-italia.com)

**680 CR 2+2**

**RM06800N335**

**Spring loaded bottom trolley**

Body in AlMg3 light alloy sheet, anodized (10 micron). Self-levelling platform with 2 side die-cast elements, complete with nylon rolls fit for sliding in light alloy rails, and 1 steel spring. Weight indicator. Strong non-twisting bottom iron frame in epoxy finishing. 2 fixed and 2 swivelling wheels with non-marking rubber ring and zinc-plated housings.



<b>Internal dimensions</b>	1470 x 900 x 585 mm h
<b>External dimensions</b>	1550 x 930 x 850 mm h
<b>Capacity</b>	774 l 85 kg
<b>Weight</b>	72,2 kg
<b>Wheels diameter</b>	125 mm
<b>Wheels position</b>	2 + 2