

# Tumble dryer

## T5350

### Features and benefits

- High productivity - 2 full loads per hour
- Low energy consumption for optimal efficiency
- Large door opening for easy loading and unloading
- Large selfcleaning lint screen for easy maintenance
- Reversible door hanging for a convenient laundry flow
- Easy access to vital parts from front and rear for simple servicing
- With Compass Pro program control
  - Large display and one control knob for easy program selection
  - Language selection
  - Quick selection and option buttons for the most frequently used drying programs and options
  - Drying program packages optimized for Economy, Care and Time and option buttons for selection of dryness
  - Service program for adjustment of parameters
  - USB connection
- The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption

### Main options

- Stainless steel front
- Stainless steel drum
- Residual Moisture Control - RMC
- Reversing drum
- Payment: coinmeter with Ecopower, chipcard reader, CP connection
- Special versions (dryer + option package): Lagoon® variant includes stainless steel front, stainless steel drum, RMC and reversing drum
- Fresh air intake
- Supply disconnecter
- CMIS (Certus Management Information System)



Images shown are a representation of the product only and variations may occur.

Main specifications			T5350			
Rated capacity,	filling factor 1:18	kg/lb	19.4/42.8			
	filling factor 1:22	kg/lb	15.5/34.2			
Drum volume		litre/ft <sup>3</sup>	349/12.3			
Drum diameter		mm/inch	760 / 29 15/16			
Heating,	electric	kW	13.5/18			
	gas	BTU/h (kW)	71700 (21)			
	steam at 800 kPa		25			
<b>Consumption data*</b>			13.5 kW	18 kW	Gas	Steam
Total time full load		min	38	27	24	22
Energy consumption full load		kWh	8.2	7.7	8.4	11.7
Evaporation		oz/min	7.4	10.2	12.1	12.7
Energy kWh/litre water evaporated		kWh/gallon	3.86	3.75	3.90	5.60

\* At rated capacity 100% cotton load at 50% initial moisture dried to 0%.

Electrical connections					
Heating alternative	Main voltage		Heating power kW	Total power kW	Recommended ITCB A
		Hz			
Electric heated	208-240V 3 ~	60	13.5/18.0	14.6/19.1	50/60
	440V 3 ~	60	13.5/18.0	14.6/19.1	30/35
	480V 3 ~	60	13.5/18.0	14.6/19.1	25/35
Gas heated/ Steam heated	208-480V 1/3 ~	60	-	1.1	15

Steam, gas and air connections			T5350
Steam		ISO 7/1-R	1"
Steam pressure		psi	14.5-145
Steam consumption		lb/h	143.3
Condensate		ISO 7/1-R	1"
Gas		ISO 7/1-R	1/2"
Gas pressure	Natural gas	psi	0.29
		mbar	20
	Propane	psi	0.40-0.73
		mbar	28-50
Air outlet		ø mm/inch	200 / 7 7/8
Evacuated air,	el 13.5 kW		21189
	el 18 kW		35315
	gas 21 kW		35315
	steam		35315
Pressure drop	el 13.5 kW	Max. psi	0.075
	el 18 kW/gas 21 kW/steam		0.039
Sound levels			
Airborne sound level		dB(A)	<70
Heat emission			
% of installed power, max			15
Shipping data*			
Weight		net, kg/lbs	177 / 390
Shipping volume		crated, m <sup>3</sup> /ft <sup>3</sup>	1.96 / 69
Dimensions in mm/inch			
A	Width		790 / 31 1/8
B(a)	Depth, el and gas		1177 / 46 5/16
B(b)	Depth, steam		1344 / 52 15/16
C	Height		1770 / 69 11/16
D			785 / 30 7/8
E			840 / 33 1/16
F			108 / 4 1/4
G			66 / 2 5/8
H			278 / 10 15/16
I			171 / 6 3/4
J			172 / 6 3/4
K			395 / 15 9/16
L			605 / 23 13/16
M			747 / 29 7/16
1	Operating panel		
2	Door opening ø 580 mm / 22 13/16 inch		
3	Electrical connection		
4	Gas connection		
5	Exhaust connection		
6	Steam: in		
7	Steam: out		

\* Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

