

Tumble dryer

T5250

Features and benefits

- High productivity – 2 full loads per hour
- Low energy consumption for optimal efficiency
- Large door opening for easy loading and unloading
- Large selfcleaning lint screen for easy maintenance
- Reversible door hanging for a convenient laundry flow
- Easy access to vital parts from front and rear for simple servicing
- With Compass Pro program control
 - Large display and one control knob for easy program selection
 - Language selection
 - Quick selection and option buttons for the most frequently used drying programs and options
 - Drying program packages optimized for Economy, Care and Time and option buttons for selection of dryness
 - Service program for adjustment of parameters
 - USB connection
- The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption

Main options

- Stainless steel front
- Stainless steel drum
- Residual Moisture Control – RMC
- Reversing drum
- Payment: coinmeter with Ecopower, chipcard reader, CP connection
- Special versions (dryer + option package): Lagoon® variant includes stainless steel front, stainless steel drum, RMC and reversing drum
- Fresh air intake
- Supply disconnecter
- CMIS (Certus Management Information System)



Images shown are a representation of the product only and variations may occur.

Main specifications			T5250				
Rated capacity, filling factor 1:18	kg/lb		13.9/30.7				
	filling factor 1:22	kg/lb	11.4/25.1				
Drum volume	litre/ft ³		250/8.8				
Drum diameter	mm/inch		760 / 29 15/16				
Heating,	electric	kW	6.0/9.0/13.5				
	gas	BTU/h (kW)	46000 (13.5)				
	steam at 800 kPa		25				
Consumption data*			6.0 kW**	9.0 kW	13.5 kW	Gas	Steam
Total time full load	min		36	36	27	27	18
Energy consumption full load	kWh		3.9	5.5	5.8	6.2	13
Evaporation	oz/min		3.9	5.6	7.5	7.4	11.5
Energy kWh/litre water evaporated	kWh/gallon		3.71	3.60	3.86	4.13	8.44

* At rated capacity 1:22, 100% cotton load at 50% initial moisture dried to 0%.

** Test load 8.2 kg/18lb

Electrical connections					
Heating alternative	Main voltage		Heating power kW	Total power kW	Recommended ITCB A
		Hz			
Electric heated	208-240V 1 -	60	6.0	7.1	40
	208-240V 3 -	60	9.0/13.5	10.1/14.6	35/50
	440V 3 -	60	9.0/13.5	10.1/14.6	20/30
	480V 3 -	60	9.0/13.5	10.1/14.6	20/25
Gas heated/ Steam heated	208-480V 1/3 -	60	-	1.1	15

Steam, gas and air connections			T5250
Steam	ISO 7/1-R		1"
Steam pressure	psi		14.5-145
Steam consumption	lb/h		143.3
Condensate	ISO 7/1-R		1"
Gas	ISO 7/1-R		1/2"
Gas pressure	Natural gas	psi	0.29
		mbar	20
	Propane	psi	0.40-0.73
		mbar	28-50
Air outlet	ø mm/inch		200 / 7 7/8
Evacuated air,	el 6/9 kW		12713
	el 13.5 kW		21189
	gas 13.5 kW		21189
	steam		35315
Pressure drop	el 6/9 kW	Max. psi	0.094
	el/gas 13.5 kW		0.075
	el 18 kW/gas 21 kW/steam		0.039
Sound levels			
Airborne sound level	dB(A)		<70
Heat emission			
% of installed power, max			15
Shipping data*			
Weight	net, kg/lbs		167 / 368
Shipping volume	crated, m ³ /ft ³		1.62 / 57
Dimensions in mm/inch			
A	Width		790 / 31 1/8
B(a)	Depth, el and gas		958 / 37 11/16
B(b)	Depth, steam		1125 / 44 5/16
C	Height		1770 / 69 11/16
D			785 / 30 7/8
E			840 / 33 1/16
F			108 / 4 1/4
G			66 / 2 5/8
H			278 / 10 15/16
I			171 / 6 3/4
J			172 / 6 3/4
K			395 / 15 9/16
L			605 / 23 13/16
M			747 / 29 7/16
N			711 / 28
1	Operating panel		
2	Door opening ø 580 mm / 22 13/16 inch		
3	Electrical connection		
4	Gas connection		
5	Exhaust connection		
6	Steam: in		
7	Steam: out		

* Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

